



Venture Tape™ UL181A-P and UL181B-FX Aluminum Foil Tape 1581A

Technical Data

September 2017

Product Description 3M™ Venture Tape™ UL181A-P and UL181B-FX Aluminum Foil Tape 1581A is a UL printed high temperature, high strength aluminum foil tape coated with a cold weather acrylic pressure sensitive adhesive.

Product Construction	Backing	Adhesive	Color	Liner	Standard Roll Length
	UL printed high strength aluminum foil	Acrylic	Natural Aluminum	Paper	60 yds (55m)

- Features**
- Conformable foil applies easily to both rigid duct board and flexible duct
 - Excellent performance in demanding temperature and humidity conditions
 - Excellent performance and durability over a wide range of environmental conditions
 - Easy to install on site without special tools or application methods

Typical Physical Properties Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Test	Typical Value	Typical Value (Metric)	Test Method
Total Tape Thickness	3.9 mils	0.09 mm	ASTM-D3652
Backing Thickness	2.0 mils	0.05 mm	ASTM-D3652
Peel Adhesion	60 oz/in	16.7 N/25mm	ASTM-D3330
Tensile Strength	29 lb/in	129 N/25 mm	ASTM-D3759
Elongation	10%	10%	ASTM-D3759
Service Temperature	-40 to 300°F	-40 to 149°C	

- Application Ideas**
- Vapor seal on reinforced fiberglass duct board
 - High performance duct closure
 - Sealing flexible duct to rigid duct

- Classifications**
- UL181A-P Listed (UL File # MH16587)
 - UL181B-FX Listed (UL File # MH16587)
 - ULC S102 Listed (Flame/Smoke 0/0) [ULC File # R10984]

3M™ Venture Tape™ UL181A-P and UL181B-FX Aluminum Foil Tape 1581A

Storage Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended.

Shelf Life To obtain best performance, use this product within 24 months from date of manufacture.

Technical Information The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection And Use Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

ISO 9001

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.



Industrial Adhesives and Tapes Division
3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/construction

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2017 All rights reserved.